

armac-

RACK PF 1.0

ON-LINE UPS



*The package includes one UPS and Tower stands for vertical mounting.
**In optionality (not shown) UPS can be installed Tower rack mounts or phone.



PRODUCT FEATURES:

- Highest Power Factor 1.0
- Pure sine wave (PSW)
- AC/DC transfer time of 0 ms
- Increased battery life with automatic test function every 60 days
- PowerManager II software allows to make commands, and monitor the operation of the device
- 8 pcs of IEC 320 C13 output sockets enable to protect several devices at the same time

PRODUCT SPECIFICATION:

UPS topology	On-line (VFI)
Power	2 000 W
Apparent power	2 000 VA
PowerFactor	1
Device efficiency	90 %
Type of casing	Rack
Number of outlets	8
Outlet type	IEC C13
Battery quantity	6
Connectors	RS-232, USB Type-B
Battery pack connector	Yes
Battery capacity	9 Ah
Battery type	Lead acid VRLA AGM
Battery voltage	12 V
Recharge time	6 h
Input voltage range	from 110 up to 300 V
Input frequency range	from 50 up to 60 Hz
Output voltage	230 V
Output acceptable voltage range	from 208 up to 240 V
Output frequency	50 Hz
Automatic Voltage Regulation (AVR)	Yes
Waveform type	Full sine wave
Transfer time	from 0 up to 0 ms
Software	PowerManager II
Size	19"
ICT height	2 U
Dimensions	505 x 438 x 88 mm
Weight	22,9 kg

EAN-13: 5901969429992
CAT. NO: R/2000I/PF1

Despite all efforts, the manufacturer / distributor / seller does not guarantee that the published technical data, photos and descriptions do not contain any deficiencies or mistakes. The above catalogue is for information purposes and does not constitute an offer within the meaning of the Civil Code.