

## RACK PF 1.0

ON-LINE UPS



\*The package includes one UPS and Tower stands for vertical mounting.  
-to coprocessors (and other) UPS (once positioned) Tower cool monitors in phone.



### PRODUCT FEATURES:

- Highest Power Factor 1.0
- Pure sine wave (PSW)
- AC/DC transfer time of 0 ms
- Increased battery life with automatic test function every 60 days
- PowerManager II software allows to make commands, and monitor the operation of the device
- 8 pcs of IEC 320 C13 output sockets enable to protect several devices at the same time

### PRODUCT SPECIFICATION:

<b>UPS topology</b>	On-line (VFI)
<b>Power</b>	3 000 W
<b>Apparent power</b>	3 000 VA
<b>PowerFactor</b>	1
<b>Device efficiency</b>	90 %
<b>Type of casing</b>	Rack
<b>Number of outlets</b>	8
<b>Outlet type</b>	IEC C13
<b>Battery quantity</b>	6
<b>Connectors</b>	RS-232, USB Type-B
<b>Battery pack connector</b>	Yes
<b>Battery capacity</b>	9 Ah
<b>Battery type</b>	Lead acid VRLA AGM
<b>Battery voltage</b>	12 V
<b>Recharge time</b>	6 h
<b>Input voltage range</b>	from 110 up to 300 V
<b>Input frequency range</b>	from 50 up to 60 Hz
<b>Output voltage</b>	230 V
<b>Output acceptable voltage range</b>	from 208 up to 240 V
<b>Output frequency</b>	50 Hz
<b>Automatic Voltage Regulation (AVR)</b>	Yes
<b>Waveform type</b>	Full sine wave
<b>Transfer time</b>	from 0 up to 0 ms
<b>Software</b>	PowerManager II
<b>Size</b>	19"
<b>ICT height</b>	2 U
<b>Dimensions</b>	505 x 438 x 88 mm
<b>Weight</b>	23,3 kg